

## Technical data

|                               |                       |
|-------------------------------|-----------------------|
| Rated voltage                 | 230V AC               |
| Input voltage range           | 100 - 240 V AC        |
| Driver output                 | 350mA                 |
| Class                         | 1                     |
| IP                            | 65                    |
| IK                            | 10                    |
| Diffuser                      | Clear polycarbonate   |
| Bulb cover                    | No                    |
| Source                        | Built-in LED          |
| Color temperature real output | 2700°K warm white SYM |
| Real light output             | 797 lm                |
| Total consumption             | 12 W                  |
| Energy class                  | -                     |
| Luminous efficacy             | 66                    |
| IRC                           | >80                   |
| SDCM                          | 5                     |
| Dimmable                      | No                    |
| Ta                            | -                     |
| Led lifetime                  | 72000 h (L80/B10)     |
| Ambient temperature range     | -10 ~50°C             |
| UGR                           | -                     |
| ULR                           | 1.0%                  |
| Photobiological Risk group    | RG0                   |
| Fixing kit                    | Yes                   |
| With sensor                   | No                    |
| With IP55 socket              | Yes                   |

[Download the installation manual](#)



### Materials and finishes

|          |                 |
|----------|-----------------|
| Material | aluminium       |
| Colour   | Dark grey - 006 |

### Logistic data

|                      |                    |
|----------------------|--------------------|
| Product dimensions   | H.1100 L.170 P.100 |
| Net weight           | 6.580 Kg           |
| Gross weight         | 7.500 Kg           |
| Package dimensions 1 | H.1140 L.200 P.130 |

### Certifications and warranties

|                |                         |
|----------------|-------------------------|
| CE             | Yes                     |
| UL             | No                      |
| EAC            | Yes                     |
| RoHS           | Yes                     |
| ENEC           | No                      |
| Anti-corrosion | 25 years (on Aluminium) |
| Technical      | 5 years                 |
| Electronics    | 3 years                 |