

Technical data

Rated voltage	230V AC
Input voltage range	230 - 250 V AC
Driver output	-
Alimentation output	-
Class	1
IP	44
IK	-
Diffuser	Polycarbonate
Bulb cover	-
Source	E27
Color temperature real output	-
Real light output	- lm
Energy class	Classe de la lampe (non fournie)
IRC	-
SDCM	-
Optic	-
Dimmable	-
Ta	-
Led lifetime	-
Ambient temperature range	-10 ~50°C
UGR	-
ULR	-
THDI	-
Fixing kit	Yes
With sensor	No
With IP55 socket	No

[Download the installation manual](#)



Kerlouan

catalogue 2024 p. 156

ref. 128009019

EAN. 3663660070201

Model 8



Materials and finishes

Material	aluminium
Colour	British green - 019 - RAL 6009

Logistic data

Product dimensions	H.2251 L.758 P.758
Net weight	7.710 Kg
Gross weight	11.190 Kg
Package dimensions 1	H.270 L.270 P.2200
Package dimensions 1	H.470 L.350 P.200
Package dimensions 3	H.470 L.350 P.200
Package dimensions 4	H.470 L.350 P.200

Certifications and warranties

CE	Yes
UL	No
EAC	Yes
RoHS	Yes
ENEC	No
Anti-corrosion	25 years (on Aluminium)
Technical	5 years
Electronics	5 years