

Avenue 4

catalogue 2024 p. 264

ref. 104251008

EAN. 3663660241915

Model 2



Technical data

Rated voltage	230V AC
Input voltage range	120 - 277 V AC
Driver output	-
Alimentation output	-
Class	1
IP	44
IK	-
Diffuser	Opal PMMA
Bulb cover	-
Source	Built-in LED
Color temperature real output	3000°K warm white
Real light output	2596 lm
Total consupction	35 W
Standby power	-
Energy class	C (Source LED)
Luminous efficacy	74
IRC	82
SDCM	-
Optic	-
Dimmable	No
Ta	-
Led lifetime	50000 h (L90/B50)
Ambient temperature range	-10 ~50°C
UGR	-
ULR	-
Photobiological Risk group	-
THDI	-
Fixing kit	Yes
With sensor	No
With IP55 socket	No

[Download the installation manual](#)



Avenue 4

catalogue 2024 p. 264

ref. 104251008

EAN. 3663660241915

Model 2



Materials and finishes

Material	aluminium
Colour	Green patina - 008

Logistic data

Product dimensions	H.657 L.365 P.188
Net weight	2.790 Kg
Gross weight	5.000 Kg
Package dimensions 1	H.640 L.430 P.260

Certifications and warranties

CE	No
UL	No
EAC	Yes
RoHS	Yes
ENEC	No
Anti-corrosion	25 years (on Aluminium)
Technical	5 years
Electronics	5 years