

Hector

catalogue 2024 p. 42

ref. 182046065

EAN. 3663660318778

Model 3



Technical data

Rated voltage	230V AC
Input voltage range	120 - 277 V AC
Driver output	600mA
Alimentation output	-
Class	1
IP	65
IK	-
Diffuser	Toughened clear glass
Bulb cover	-
Source	Built-in LED
Color temperature real output	2700°K warm white ASYM
Real light output	4250 lm
Total consupction	32 W
Energy class	C (Source LED)
Luminous efficacy	132.8
IRC	73
SDCM	-
Optic	-
Dimmable	1 to 10 Volt
Ta	-
Led lifetime	50000 h (L90/B50)
Ambient temperature range	-10 ~50°C
UGR	-
ULR	< 0.1%
Photobiological Risk group	RG0
THDI	-
Fixing kit	Anchor bolts on request
With sensor	No
With IP55 socket	No

[Download the installation manual](#)



Hector

catalogue 2024 p. 42

ref. 182046065

EAN. 3663660318778

Model 3



Materials and finishes

Material	aluminium
Colour	Steel blue - 065 - RAL 5011

Logistic data

Product dimensions	H.4026 L.260 P.427
Net weight	14.200 Kg
Gross weight	16.360 Kg
Package dimensions 1	H.168 L.170 P.385

Certifications and warranties

CE	Yes
UL	No
EAC	Yes
RoHS	Yes
ENEC	No
Anti-corrosion	25 years (on Aluminium)
Technical	5 years
Electronics	5 years