

RP 195

catalogue 2024 p. 92

ref. 153008082

EAN. 3663660233279

Model 4

Technical data

Rated voltage	200 to 240 - 50/60Hz
Input voltage range	230 - 250 V AC
Driver output	-
Alimentation output	-
Class	1
IP	65
IK	-
Diffuser	Frosted glass
Bulb cover	-
Source	E27
Color temperature real output	-
Real light output	- lm
Energy class	Classe de la lampe (non fournie)
IRC	-
SDCM	-
Optic	-
Dimmable	-
Ta	-
Led lifetime	-
Ambient temperature range	-10 ~50°C
UGR	-
ULR	-
THDI	-
Fixing kit	Yes
With sensor	No
With IP55 socket	No

[Download the installation manual](#)



RP 195

catalogue 2024 p. 92

ref. 153008082

EAN. 3663660233279

Model 4



Materials and finishes

Material	copper
Colour	Raw copper - 082

Logistic data

Product dimensions	H.602 L.145 P.243
Net weight	2.930 Kg
Gross weight	0.000 Kg
Package dimensions 1	H.250 L.250 P.950

Certifications and warranties

CE	Yes
UL	No
EAC	Yes
RoHS	Yes
ENEC	No
Anti-corrosion	25 years (on Aluminium)
Technical	5 years
Electronics	5 years