

Avenue 3

catalogue 2024 p. 258

ref. 103161000

EAN. 3663660311663

Model 2



Technical data

Rated voltage	230V AC
Input voltage range	100 - 240 V AC
Driver output	350mA
Alimentation output	-
Class	1
IP	44
IK	-
Diffuser	Clear glass
Bulb cover	-
Source	Built-in LED
Color temperature real output	3000°K warm white
Real light output	1727 lm
Total consupction	35 W
Standby power	-
Energy class	E (Source LED)
Luminous efficacy	49
IRC	>80
SDCM	-
Optic	-
Dimmable	No
Ta	-
Led lifetime	50000 h (L90/B50)
Ambient temperature range	-10 ~50°C
UGR	-
ULR	-
Photobiological Risk group	-
THDI	-
Fixing kit	Yes
With sensor	No
With IP55 socket	No

[Download the installation manual](#)



Avenue 3

catalogue 2024 p. 258

ref. 103161000

EAN. 3663660311663

Model 2



Materials and finishes

Material	aluminium
Colour	Jet black - 000 - RAL 9005

Logistic data

Product dimensions	H.3619 L.282 P.282
Net weight	2.200 Kg
Gross weight	2.820 Kg
Package dimensions 1	H.250 L.250 P.3000
Package dimensions 1	H.340 L.340 P.880

Certifications and warranties

CE	Yes
UL	No
EAC	Yes
RoHS	Yes
ENEC	No
Anti-corrosion	25 years (on Aluminium)
Technical	5 years
Electronics	5 years