

Tetra

catalogue 2024 p. 48

ref. 162133101

EAN. 3663660277006

Model 4

Technical data

| | |
|-------------------------------|------------------------|
| Rated voltage | 230V AC |
| Input voltage range | 100 - 240 V AC |
| Driver output | 350mA |
| Class | 1 |
| IP | 65 |
| IK | 10 |
| Diffuser | Clear polycarbonate |
| Bulb cover | No |
| Source | Built-in LED |
| Color temperature real output | 2700°K warm white ASYM |
| Real light output | 879 lm |
| Total consumption | 12 W |
| Energy class | - |
| Luminous efficacy | 73,3 |
| IRC | >80 |
| SDCM | 5 |
| Dimmable | No |
| Ta | - |
| Led lifetime | 72000 h (L80/B10) |
| Ambient temperature range | -10 ~50°C |
| UGR | - |
| ULR | 1.0% |
| Photobiological Risk group | RG0 |
| Fixing kit | Yes |
| With sensor | No |
| With IP55 socket | Yes |

[Download the installation manual](#)



Tetra

catalogue 2024 p. 48

ref. 162133101

EAN. 3663660277006

Model 4



Materials and finishes

| | |
|----------|------------------|
| Material | aluminium |
| Colour | Pure white - 101 |

Logistic data

| | |
|----------------------|--------------------|
| Product dimensions | H.1100 L.170 P.100 |
| Net weight | 6.580 Kg |
| Gross weight | 7.500 Kg |
| Package dimensions 1 | H.1140 L.200 P.130 |

Certifications and warranties

| | |
|----------------|-------------------------|
| CE | Yes |
| UL | No |
| EAC | Yes |
| RoHS | Yes |
| ENEC | No |
| Anti-corrosion | 25 years (on Aluminium) |
| Technical | 5 years |
| Electronics | 3 years |