

Technical data

| | |
|-------------------------------|----------------------------------|
| Rated voltage | 200 to 240 - 50/60Hz |
| Input voltage range | 230 - 250 V AC |
| Driver output | - |
| Alimentation output | - |
| Class | 1 |
| IP | 44 |
| IK | - |
| Diffuser | Frosted glass |
| Bulb cover | - |
| Source | E27 |
| Color temperature real output | - |
| Real light output | - lm |
| Total consumption | - W |
| Energy class | Classe de la lampe (non fournie) |
| Luminous efficacy | - |
| IRC | - |
| SDCM | - |
| Optic | - |
| Dimmable | - |
| Ta | - |
| Led lifetime | - |
| Ambient temperature range | -10 ~50°C |
| UGR | - |
| ULR | - |
| THDI | - |
| Fixing kit | Yes |
| With sensor | No |
| With IP55 socket | No |

[Download the installation manual](#)



Materials and finishes

| | |
|----------|------------|
| Material | aluminium |
| Colour | Blue - 111 |

Logistic data

| | |
|----------------------|-------------------|
| Product dimensions | H.328 L.251 P.280 |
| Net weight | 1.200 Kg |
| Gross weight | 2.110 Kg |
| Package dimensions 1 | H.340 L.300 P.400 |

Certifications and warranties

| | |
|----------------|-------------------------|
| CE | Yes |
| UL | No |
| EAC | Yes |
| RoHS | Yes |
| ENEC | No |
| Anti-corrosion | 25 years (on Aluminium) |
| Technical | 5 years |
| Electronics | 5 years |