

## Technical data

|                           |                            |
|---------------------------|----------------------------|
| Rated voltage             | 230V AC                    |
| Input voltage range       | 230 - 250 V AC             |
| Class                     | 1                          |
| IP                        | 44                         |
| IK                        | -                          |
| Diffuser                  | -                          |
| Bulb cover                | -                          |
| Source                    | no sources - FRENCH SOCKET |
| Real light output         | - lm                       |
| Energy class              | -                          |
| SDCM                      | -                          |
| Ta                        | -                          |
| Ambient temperature range | -10 ~50°C                  |
| UGR                       | -                          |
| ULR                       | -                          |
| Fixing kit                | Yes                        |
| With sensor               | No                         |
| With IP55 socket          | Yes                        |

[Download the installation manual](#)



## Materials and finishes

|          |                            |
|----------|----------------------------|
| Material | aluminium                  |
| Colour   | Fir green - 067 - RAL 6009 |

## Logistic data

|                      |                   |
|----------------------|-------------------|
| Product dimensions   | H.371 L.136 P.136 |
| Net weight           | 0.990 Kg          |
| Gross weight         | 1.350 Kg          |
| Package dimensions 1 | H.410 L.190 P.140 |

## Certifications and warranties

|                |                         |
|----------------|-------------------------|
| CE             | Yes                     |
| UL             | No                      |
| EAC            | Yes                     |
| RoHS           | Yes                     |
| ENEC           | No                      |
| Anti-corrosion | 25 years (on Aluminium) |
| Technical      | 5 years                 |
| Electronics    | 5 years                 |