

Hector

catalogue 2024 p. 42

ref. 182014046

EAN. 3663660266567

Model 2



Technical data

Rated voltage	230V AC
Input voltage range	120 - 277 V AC
Driver output	500mA
Alimentation output	-
Class	1
IP	65
IK	-
Diffuser	Toughened clear glass
Bulb cover	-
Source	Built-in LED
Color temperature real output	3000°K warm white ASYM
Real light output	3270 lm
Total consupction	26 W
Energy class	C (Source LED)
Luminous efficacy	125.8
IRC	73
SDCM	-
Optic	-
Dimmable	No
Ta	-
Led lifetime	50000 h (L90/B50)
Ambient temperature range	-10 ~50°C
UGR	-
ULR	< 0.1%
Photobiological Risk group	RG0
THDI	-
Fixing kit	Anchor bolts on request
With sensor	No
With IP55 socket	No



[Download the installation manual](#)

Materials and finishes

Material	aluminium
Colour	Old rustic - 046

Logistic data

Product dimensions	H.3026 L.260 P.427
Net weight	0.000 Kg
Gross weight	0.000 Kg
Package dimensions 1	H.168 L.170 P.385

Certifications and warranties

CE	Yes
UL	No
EAC	Yes
RoHS	Yes
ENEC	No
Anti-corrosion	25 years (on Aluminium)
Technical	5 years
Electronics	5 years