

Avenue 4

catalogue 2024 p. 264

ref. 104262008

EAN. 3663660303330

Model 6



Technical data

Rated voltage	230V AC
Input voltage range	100 - 240 V AC
Driver output	-
Alimentation output	-
Class	1
IP	65
IK	-
Diffuser	Opal PMMA
Bulb cover	-
Source	Built-in LED
Color temperature real output	3000°K warm white
Real light output	2693 lm
Total consupction	37,4 W
Energy class	E (Source LED)
Luminous efficacy	72
IRC	>80
SDCM	-
Optic	-
Dimmable	No
Ta	-
Led lifetime	-
Ambient temperature range	-10 ~50°C
UGR	-
ULR	-
Photobiological Risk group	-
THDI	-
Fixing kit	Anchor bolts on request
With sensor	No
With IP55 socket	No

[Download the installation manual](#)



Avenue 4

catalogue 2024 p. 264

ref. 104262008

EAN. 3663660303330

Model 6



Materials and finishes

Material	aluminium
Colour	Green patina - 008

Logistic data

Product dimensions	H.1004 L.364 P.364
Net weight	9.750 Kg
Gross weight	0.000 Kg
Package dimensions 1	H.420 L.420 P.890
Package dimensions 1	H.350 L.350 P.260

Certifications and warranties

CE	Yes
UL	No
EAC	Yes
RoHS	Yes
ENEC	No
Anti-corrosion	25 years (on Aluminium)
Technical	5 years
Electronics	5 years