

Technical data

Rated voltage	230V AC
Input voltage range	120 - 277 V AC
Driver output	700mA
Alimentation output	-
Class	1
IP	55
IK	-
Diffuser	Toughened borosilicate glass
Bulb cover	-
Source	Built-in LED
Color temperature real output	4000°K neutral white
Real light output	3855 lm
Total consupction	42 W
Energy class	C (Source LED)
Luminous efficacy	92
IRC	83
SDCM	-
Optic	-
Dimmable	No
Ta	-
Led lifetime	50000 h (L90/B50)
Ambient temperature range	-10 ~50°C
UGR	-
ULR	-
Photobiological Risk group	No
THDI	-
Fixing kit	No
With sensor	No
With IP55 socket	No
Cable with plug	F

[Download the installation manual](#)



Materials and finishes

Material	aluminium
Colour	Wine red - 066 - RAL 3005

Logistic data

Product dimensions	H.2269 - 2669 L.723 P.1047
Net weight	32.380 Kg
Gross weight	38.580 Kg
Package dimensions 1	H.800 L.390 P.630
Package dimensions 1	H.1970 L.280 P.300

Certifications and warranties

CE	Yes
UL	No
EAC	Yes
RoHS	Yes
ENEC	No
Anti-corrosion	25 years (on Aluminium)
Technical	5 years
Electronics	5 years