


Technical data

Rated voltage	230V AC
Input voltage range	120 - 277 V AC
Driver output	700mA
Alimentation output	-
Class	1
IP	65
IK	-
Diffuser	Toughened clear glass
Bulb cover	-
Source	Built-in LED
Color temperature real output	3000°K warm white SYM
Energy class	C (Source LED)
IRC	74
SDCM	-
Optic	-
Dimmable	DALI
Ta	-
Led lifetime	50000 h (L90/B50)
Ambient temperature range	-10 ~50°C
UGR	-
ULR	< 0.1 %
Photobiological Risk group	RG0
THDI	-
Fixing kit	Yes
With sensor	No
With IP55 socket	No



[Download the installation manual](#)

Hector

catalogue 2024 p. 42

ref. 182305056

EAN. 3663660278492

Model 1



Materials and finishes

Material	aluminium
Colour	Traffic red - 056 - RAL 3020

Logistic data

Product dimensions	H.143 L.160 P.366
Net weight	2.380 Kg
Gross weight	2.690 Kg
Package dimensions 1	H.168 L.170 P.385

Certifications and warranties

CE	Yes
UL	No
EAC	Yes
RoHS	Yes
ENEC	No
Anti-corrosion	25 years (on Aluminium)
Technical	5 years
Electronics	5 years