

## Technical data

|                               |                         |
|-------------------------------|-------------------------|
| Rated voltage                 | 230V AC                 |
| Input voltage range           | 120 - 277 V AC          |
| Driver output                 | 700mA                   |
| Alimentation output           | -                       |
| Class                         | 1                       |
| IP                            | 65                      |
| IK                            | -                       |
| Diffuser                      | Toughened clear glass   |
| Bulb cover                    | -                       |
| Source                        | Built-in LED            |
| Color temperature real output | 3000°K warm white ASYM  |
| Energy class                  | C (Source LED)          |
| IRC                           | 73                      |
| SDCM                          | -                       |
| Optic                         | -                       |
| Dimmable                      | DALI                    |
| Ta                            | -                       |
| Led lifetime                  | 50000 h (L90/B50)       |
| Ambient temperature range     | -10 ~50°C               |
| UGR                           | -                       |
| ULR                           | < 0.1 %                 |
| Photobiological Risk group    | RG0                     |
| THDI                          | -                       |
| Fixing kit                    | Anchor bolts on request |
| With sensor                   | No                      |
| With IP55 socket              | No                      |

[Download the installation manual](#)



# Hector

catalogue 2024 p. 42

ref. 182218056

EAN. 3663660278157

Model 2



## Materials and finishes

|          |                              |
|----------|------------------------------|
| Material | aluminium                    |
| Colour   | Traffic red - 056 - RAL 3020 |

## Logistic data

|                      |                    |
|----------------------|--------------------|
| Product dimensions   | H.3026 L.260 P.427 |
| Net weight           | 12.460 Kg          |
| Gross weight         | 13.520 Kg          |
| Package dimensions 1 | H.168 L.170 P.385  |

## Certifications and warranties

|                |                         |
|----------------|-------------------------|
| CE             | Yes                     |
| UL             | No                      |
| EAC            | Yes                     |
| RoHS           | Yes                     |
| ENEC           | No                      |
| Anti-corrosion | 25 years (on Aluminium) |
| Technical      | 5 years                 |
| Electronics    | 5 years                 |