

Technical data

Rated voltage	200 to 240 - 50/60Hz
Input voltage range	230 - 250 V AC
Driver output	-
Alimentation output	-
Class	1
IP	44
IK	-
Diffuser	Clear glass
Bulb cover	-
Source	E27
Color temperature real output	-
Real light output	- lm
Energy class	Classe de la lampe (non fournie)
IRC	-
SDCM	-
Optic	-
Dimmable	-
Ta	-
Led lifetime	-
Ambient temperature range	-10 ~50°C
UGR	-
ULR	-
THDI	-
Fixing kit	Yes
With sensor	No
With IP55 socket	No

[Download the installation manual](#)



Materials and finishes

Material	copper
Colour	Varnished brushed copper - 084
Colour of the support	Velvet black - 113

Logistic data

Product dimensions	H.2196 L.855 P.320
Net weight	8.950 Kg
Gross weight	10.800 Kg
Package dimensions 1	H.270 L.270 P.2200
Package dimensions 1	H.510 L.360 P.260
Package dimensions 3	H.510 L.360 P.260

Certifications and warranties

CE	Yes
UL	No
EAC	Yes
RoHS	Yes
ENEC	No
Anti-corrosion	25 years (on Aluminium)
Technical	5 years
Electronics	5 years