

Avenue 2

catalogue 2024 p. 252

ref. 102115070

EAN. 3663660290517

Model 5



Technical data

Rated voltage	230V AC
Input voltage range	100 - 240 V AC
Driver output	700mA
Alimentation output	-
Class	1
IP	44
IK	-
Diffuser	Opal PMMA
Bulb cover	-
Source	Built-in LED
Color temperature real output	2700°K warm white
Real light output	677 lm
Total consupction	13 W
Energy class	D (Source LED)
Luminous efficacy	52
IRC	83
SDCM	-
Optic	-
Dimmable	No
Ta	-
Led lifetime	50000 h (L90/B50)
Ambient temperature range	-10 ~50°C
UGR	-
ULR	-
Photobiological Risk group	No
THDI	-
Fixing kit	Yes
With sensor	No
With IP55 socket	No

[Download the installation manual](#)



Avenue 2

catalogue 2024 p. 252

ref. 102115070

EAN. 3663660290517

Model 5



Materials and finishes

Material	retified wood
Colour	Tinted lacquered brass - 070

Logistic data

Product dimensions	H.552 L.240 P.240
Net weight	0.000 Kg
Gross weight	0.000 Kg
Package dimensions 1	H.630 L.270 P.280

Certifications and warranties

CE	Yes
UL	No
EAC	Yes
RoHS	Yes
ENEC	No
Anti-corrosion	25 years (on Aluminium)
Technical	5 years
Electronics	5 years