

Technical data

Rated voltage	230V AC
Input voltage range	230 - 250 V AC
Driver output	-
Alimentation output	-
Class	1
IP	44
IK	10
Diffuser	Opal polycarbonate
Bulb cover	No
Source	E27
Color temperature real output	-
Real light output	- lm
Total consupcion	- W
Energy class	Classe de la lampe (non fournie)
Luminous efficacy	-
IRC	-
SDCM	-
Optic	-
Dimmable	-
Ta	-
Led lifetime	-
Ambient temperature range	-10 ~50°C
UGR	-
ULR	-
THDI	-
Fixing kit	Yes
With sensor	No
With IP55 socket	No

[Download the installation manual](#)

Dallas

catalogue 2024 p. 182

ref. 119025134

EAN. 3663660277044

Model 5



Materials and finishes

Material	aluminium
Colour	Matt azure blue - 134 - RAL 5009

Logistic data

Product dimensions	H.438 L.320 P.320
Net weight	1.870 Kg
Gross weight	3.300 Kg
Package dimensions 1	H.580 L.340 P.340

Certifications and warranties

CE	Yes
UL	No
EAC	Yes
RoHS	Yes
ENEC	No
Anti-corrosion	25 years (on Aluminium)
Technical	5 years
Electronics	5 years