OL 33

catalogue 2024 p. 132

ref. 144209107

EAN. 3663660249041

Model 3

Technical data

Rated voltage	230V AC
Input voltage range	100 - 240 V AC
Driver output	700mA
Alimentation output	-
Class	1
IP	65
IK	-
Diffuser	Toughened glass
Bulb cover	No
Source	Built-in LED
Color temperature real output	4500°K neutral white
Real light output	874 lm
Total consuption	20 W
Standby power	-
Energy class	D (Source LED)
Luminous efficacy	43.7
IRC	83
SDCM	-
Optic	Yes
Dimmable	No
Ta	-
Led lifetime	-
Ambient temperature range	-10 ~50°C
UGR	-
ULR	18%
Photobiological Risk group	-
THDI	-
Fixing kit	Yes
With sensor	No
With IP55 socket	No

Download the installation manual

OL 33

Model 3

catalogue 2024 p. 132

ref. 144209107

EAN. 3663660249041

Materials ans finishes

Material	aluminium
Colour	Black grey - 107 - RAL 7021

Logistic data

Product dimensions	H.486 L.220 P.249
Net weight	3.120 Kg
Gross weight	4.080 Kg
Package dimensions 1	H.550 L.260 P.310

Certifications and warranties

CE	Yes
UL	No
EAC	Yes
RoHS	Yes
ENEC	No
Anti-corrosion	25 years (on Aluminium)
Technical	5 years
Electronics	3 years