

## Technical data

|                               |                   |
|-------------------------------|-------------------|
| Rated voltage                 | 230V AC           |
| Input voltage range           | 120 - 277 V AC    |
| Class                         | 1                 |
| IP                            | 65                |
| IK                            | 10                |
| Diffuser                      | Satin-finish PMMA |
| Bulb cover                    | No                |
| Source                        | Built-in LED      |
| Color temperature real output | 2700°K warm white |
| Real light output             | 1952 lm           |
| Total consupction             | 26 W              |
| Energy class                  | C (Source LED)    |
| IRC                           | >80               |
| SDCM                          | 4                 |
| Dimmable                      | No                |
| Ta                            | -                 |
| Ambient temperature range     | -10 ~50°C         |
| UGR                           | -                 |
| ULR                           | -                 |
| Photobiological Risk group    | RG2               |
| Fixing kit                    | Yes               |
| With sensor                   | No                |
| With IP55 socket              | No                |

[Download the installation manual](#)



### Materials and finishes

|          |                  |
|----------|------------------|
| Material | aluminium        |
| Colour   | Old rustic - 046 |

### Logistic data

|                      |                   |
|----------------------|-------------------|
| Product dimensions   | H.400 L.260 P.183 |
| Net weight           | 2.930 Kg          |
| Gross weight         | 3.620 Kg          |
| Package dimensions 1 | H.470 L.350 P.200 |

### Certifications and warranties

|                |                         |
|----------------|-------------------------|
| CE             | Yes                     |
| UL             | No                      |
| EAC            | Yes                     |
| RoHS           | Yes                     |
| ENEC           | No                      |
| Anti-corrosion | 25 years (on Aluminium) |
| Technical      | 5 years                 |
| Electronics    | 5 years                 |