

## Technical data

|                               |                              |
|-------------------------------|------------------------------|
| Rated voltage                 | 230V AC                      |
| Input voltage range           | 120 - 277 V AC               |
| Driver output                 | 700mA                        |
| Alimentation output           | -                            |
| Class                         | 1                            |
| IP                            | 55                           |
| IK                            | -                            |
| Diffuser                      | Toughened borosilicate glass |
| Bulb cover                    | -                            |
| Source                        | Built-in LED                 |
| Color temperature real output | 4000°K neutral white         |
| Real light output             | 3855 lm                      |
| Total consupction             | 42 W                         |
| Energy class                  | C (Source LED)               |
| Luminous efficacy             | 92                           |
| IRC                           | 83                           |
| SDCM                          | -                            |
| Optic                         | -                            |
| Dimmable                      | No                           |
| Ta                            | -                            |
| Led lifetime                  | 50000 h (L90/B50)            |
| Ambient temperature range     | -10 ~50°C                    |
| UGR                           | -                            |
| ULR                           | -                            |
| Photobiological Risk group    | No                           |
| THDI                          | -                            |
| Fixing kit                    | No                           |
| With sensor                   | No                           |
| With IP55 socket              | No                           |
| Cable with plug               | F                            |

[Download the installation manual](#)



## Materials and finishes

|          |                                  |
|----------|----------------------------------|
| Material | aluminium, bicromated steel base |
| Colour   | Wine red - 066 - RAL 3005        |

## Logistic data

|                      |                            |
|----------------------|----------------------------|
| Product dimensions   | H.2269 - 2669 L.723 P.1047 |
| Net weight           | 32.380 Kg                  |
| Gross weight         | 38.580 Kg                  |
| Package dimensions 1 | H.800 L.390 P.630          |
| Package dimensions 1 | H.1970 L.280 P.300         |

## Certifications and warranties

|                |                         |
|----------------|-------------------------|
| CE             | Yes                     |
| UL             | No                      |
| EAC            | Yes                     |
| RoHS           | Yes                     |
| ENEC           | No                      |
| Anti-corrosion | 25 years (on Aluminium) |
| Technical      | 5 years                 |
| Electronics    | 5 years                 |