Lampiok 2

Model 4

catalogue 2024 p. 74

ref. 178011105

EAN. 3663660273787

Technical data

Rated voltage	200 to 240 - 50/60Hz
Input voltage range	230 - 250 V AC
Driver output	-
Alimentation output	-
Class	1
IP	65
IK	-
Diffuser	Clear glass
Bulb cover	No
Source	E27
Color temperature real output	-
Real light output	- lm
Standby power	-
Energy class	Classe de la lampe (non fournie)
IRC	-
SDCM	-
Optic	-
Dimmable	-
Ta	-
Led lifetime	-
Ambient temperature range	-10 ~50°C
UGR	-
ULR	-
Photobiological Risk group	-
THDI	-
Fixing kit	Anchor bolts on request
With sensor	No
With IP55 socket	No

Download the installation manual

Lampiok 2

Model 4

catalogue 2024 p. 74

ref. 178011105

EAN. 3663660273787

Materials ans finishes

Material	aluminium
Colour	Silk grey - 105 - RAL 7044

Logistic data

Product dimensions	H.3004 L.280 P.594
Net weight	0.000 Kg
Gross weight	0.000 Kg
Package dimensions 1	H.250 L.250 P.3000
Package dimensions 1	H.700 L.460 P.280

Certifications and warranties

CE	Yes
UL	No
EAC	Yes
RoHS	Yes
ENEC	No
Anti-corrosion	25 years (on Aluminium)
Technical	5 years
Electronics	5 years