

## Technical data

|                               |                    |
|-------------------------------|--------------------|
| Rated voltage                 | 230V AC            |
| Input voltage range           | 100 - 240 V AC     |
| Alimentation output           | -                  |
| Class                         | 1                  |
| IP                            | 65                 |
| IK                            | 07                 |
| Diffuser                      | Satin-finish PMMA  |
| Bulb cover                    | No                 |
| Source                        | Built-in LED       |
| Color temperature real output | 2700°K warm white  |
| Real light output             | 4500 lm            |
| Total consupction             | 41 W               |
| Standby power                 | -                  |
| Energy class                  | D (Source LED)     |
| Luminous efficacy             | 110                |
| IRC                           | >80                |
| SDCM                          | 3                  |
| Ta                            | -                  |
| Led lifetime                  | > 70000h (L90/B50) |
| Ambient temperature range     | -10 ~50°C          |
| UGR                           | -                  |
| ULR                           | < 1.0%             |
| Photobiological Risk group    | -                  |
| Fixing kit                    | Yes                |
| With sensor                   | No                 |
| With IP55 socket              | No                 |

[Download the installation manual](#)



### *Materials and finishes*

|          |                            |
|----------|----------------------------|
| Material | aluminium                  |
| Colour   | Silk grey - 105 - RAL 7044 |

### *Logistic data*

|                      |                    |
|----------------------|--------------------|
| Product dimensions   | H.2197 L.387 P.387 |
| Net weight           | 14.820 Kg          |
| Gross weight         | 17.150 Kg          |
| Package dimensions 1 | H.420 L.420 P.540  |

### *Certifications and warranties*

|                |                         |
|----------------|-------------------------|
| CE             | Yes                     |
| UL             | No                      |
| EAC            | Yes                     |
| RoHS           | Yes                     |
| ENEC           | No                      |
| Anti-corrosion | 25 years (on Aluminium) |
| Technical      | 5 years                 |
| Electronics    | 5 years                 |