

Lampioik 4

catalogue 2024 p. 80

ref. 175024105

EAN. 3663660291620

Model 1

Technical data

Rated voltage	230V AC
Input voltage range	100 - 240 V AC
Driver output	700mA
Alimentation output	-
Class	1
IP	65
IK	-
Diffuser	Satin-finish PMMA
Bulb cover	-
Source	Built-in LED
Color temperature real output	3000°K warm white
Real light output	4794 lm
Total consupction	36 W
Energy class	C (Source LED)
Luminous efficacy	133
IRC	73
SDCM	-
Optic	-
Dimmable	No
Ta	-
Led lifetime	50000 h (L90/B50)
Ambient temperature range	-10 ~50°C
UGR	-
ULR	-
Photobiological Risk group	No
THDI	-
Fixing kit	Yes
With sensor	No
With IP55 socket	No

[Download the installation manual](#)



Lampioik 4

catalogue 2024 p. 80

ref. 175024105

EAN. 3663660291620

Model 1



Materials and finishes

Material	aluminium
Colour	Silk grey - 105 - RAL 7044

Logistic data

Product dimensions	H.883 L.452 P.720
Net weight	7.280 Kg
Gross weight	10.820 Kg
Package dimensions 1	H.790 L.610 P.500

Certifications and warranties

CE	Yes
UL	No
EAC	Yes
RoHS	Yes
ENEC	No
Anti-corrosion	25 years (on Aluminium)
Technical	5 years
Electronics	5 years