

Technical data

Rated voltage	230V AC
Input voltage range	230 - 250 V AC
Driver output	-
Alimentation output	-
Class	1
IP	44
IK	-
Diffuser	Clear glass
Bulb cover	No
Source	E27
Color temperature real output	-
Real light output	- lm
Total consupcion	- W
Energy class	Classe de la lampe (non fournie)
Luminous efficacy	-
IRC	-
SDCM	-
Optic	-
Dimmable	-
Ta	-
Led lifetime	-
Ambient temperature range	-10 ~50°C
UGR	-
ULR	-
THDI	-
Fixing kit	Anchor bolts on request
With sensor	No
With IP55 socket	No

[Download the installation manual](#)



Materials and finishes

Material	aluminium
Colour	Gold patina - 009

Logistic data

Product dimensions	H.2617 L.797 P.797
Net weight	19.600 Kg
Gross weight	33.980 Kg
Package dimensions 1	H.1210 L.310 P.310
Package dimensions 1	H.370 L.370 P.230
Package dimensions 3	H.480 L.250 P.250
Package dimensions 4	H.480 L.250 P.250
Package dimensions 5	H.480 L.250 P.250

Certifications and warranties

CE	Yes
UL	No
EAC	Yes
RoHS	Yes
ENEC	No
Anti-corrosion	25 years (on Aluminium)
Technical	5 years
Electronics	5 years