

OL 33

catalogue 2024 p. 132

ref. 144218014

EAN. 3663660280068

Model 7

Technical data

Rated voltage	230V AC
Input voltage range	100 - 240 V AC
Driver output	700mA
Alimentation output	-
Class	1
IP	65
IK	-
Diffuser	Toughened glass
Bulb cover	No
Source	Built-in LED
Color temperature real output	4500°K neutral white
Real light output	1758 lm
Total consupction	40 W
Standby power	-
Energy class	D (Source LED)
Luminous efficacy	43.7
IRC	83
SDCM	-
Optic	Yes
Dimmable	No
Ta	-
Led lifetime	-
Ambient temperature range	-10 ~50°C
UGR	-
ULR	18%
Photobiological Risk group	-
THDI	-
Fixing kit	Anchor bolts on request
With sensor	No
With IP55 socket	No

[Download the installation manual](#)



OL 33

catalogue 2024 p. 132

ref. 144218014

EAN. 3663660280068

Model 7



Materials and finishes

Material	aluminium
Colour	Pure orange - 014 - RAL 2004

Logistic data

Product dimensions	H.3300 L.730 P.289
Net weight	15.280 Kg
Gross weight	18.210 Kg
Package dimensions 1	H.720 L.480 P.300
Package dimensions 1	H.3020 L.300 P.300

Certifications and warranties

CE	Yes
UL	No
EAC	Yes
RoHS	Yes
ENEC	No
Anti-corrosion	25 years (on Aluminium)
Technical	5 years
Electronics	3 years