

Technical data

Rated voltage	230V AC
Input voltage range	100 - 240 V AC
Driver output	350mA
Class	1
IP	65
IK	10
Diffuser	Clear polycarbonate
Bulb cover	No
Source	Green'Up socket - Built-in LED
Color temperature real output	2700°K warm white ASYM
Real light output	879 lm
Total consumption	12 W
Standby power	-
Energy class	-
Luminous efficacy	73,3
IRC	>80
SDCM	5
Optic	-
Dimmable	No
Ta	-
Tc	-
Led lifetime	72000 h (L80/B10)
Ambient temperature range	-10 ~50°C
UGR	-
ULR	1.0%
Photobiological Risk group	RG0
Fixing kit	Yes
With sensor	No
With IP55 socket	Yes

[Download the installation manual](#)



Materials and finishes

Material	aluminium
Colour	Steel blue - 065 - RAL 5011

Logistic data

Product dimensions	H.1100 L.170 P.100
Net weight	0.000 Kg
Gross weight	0.000 Kg
Package dimensions 1	H.1140 L.200 P.130

Certifications and warranties

CE	Yes
UL	No
EAC	Yes
RoHS	Yes
ENEC	No
Anti-corrosion	25 years (on Aluminium)
Technical	5 years
Electronics	3 years