

Technical data

Rated voltage	200 to 240 - 50/60Hz
Input voltage range	220 - 240 V AC
Driver output	-
Alimentation output	-
Class	1
IP	44
IK	-
Diffuser	Clear glass
Bulb cover	-
Source	E27
Color temperature real output	-
Real light output	- lm
Total consupction	- W
Standby power	-
Energy class	Classe de la lampe (non fournie)
Luminous efficacy	-
IRC	-
SDCM	-
Optic	-
Dimmable	-
Ta	-
Tc	-
Led lifetime	-
Ambient temperature range	-10 ~50°C
UGR	-
ULR	-
Photobiological Risk group	-
THDI	-
Fixing kit	Yes
With sensor	No
With IP55 socket	No

[Download the installation manual](#)



Materials and finishes

Material	aluminium
Colour	Pure white - 101 - RAL 9010

Logistic data

Product dimensions	H.1001 L.320 P.517
Net weight	6.070 Kg
Gross weight	7.980 Kg
Package dimensions 1	H.510 L.360 P.260
Package dimensions 1	H.1100 L.190 P.190

Certifications and warranties

CE	Yes
UL	No
EAC	Yes
RoHS	Yes
ENEC	No
Anti-corrosion	25 years (on Aluminium)
Technical	5 years
Electronics	5 years