

Technical data

Rated voltage	230V AC
Input voltage range	230 - 250 V AC
Driver output	-
Alimentation output	-
Class	1
IP	44
IK	-
Diffuser	Polycarbonate
Bulb cover	-
Source	E27
Color temperature real output	-
Real light output	- lm
Energy class	Classe de la lampe (non fournie)
IRC	-
SDCM	-
Optic	-
Dimmable	-
Ta	-
Led lifetime	-
Ambient temperature range	-10 ~50°C
UGR	-
ULR	-
THDI	-
Fixing kit	Yes
With sensor	Yes
With IP55 socket	No

[Download the installation manual](#)

Kerlouan

catalogue 2024 p. 156

ref. 128007059

EAN. 3663660069922

Model 4



Materials and finishes

Material	aluminium
Colour	Slate grey - 059

Logistic data

Product dimensions	H.1059 L.316 P.316
Net weight	2.900 Kg
Gross weight	4.400 Kg
Package dimensions 1	H.1100 L.190 P.190
Package dimensions 1	H.370 L.370 P.230

Certifications and warranties

CE	Yes
UL	No
EAC	Yes
RoHS	Yes
ENEC	No
Anti-corrosion	25 years (on Aluminium)
Technical	5 years
Electronics	5 years