

# Lampioik 4

catalogue 2024 p. 80

ref. 175233105

EAN. 3663660322287

Model 1



## Technical data

|                               |                   |
|-------------------------------|-------------------|
| Rated voltage                 | 230V AC           |
| Input voltage range           | 100 - 240 V AC    |
| Driver output                 | 700mA             |
| Alimentation output           | -                 |
| Class                         | 1                 |
| IP                            | 65                |
| IK                            | -                 |
| Diffuser                      | Satin-finish PMMA |
| Bulb cover                    | -                 |
| Source                        | Built-in LED      |
| Color temperature real output | 2700°K warm white |
| Real light output             | 4794 lm           |
| Total consupction             | 36 W              |
| Energy class                  | C (Source LED)    |
| Luminous efficacy             | 133               |
| IRC                           | 73                |
| SDCM                          | -                 |
| Optic                         | -                 |
| Dimmable                      | No                |
| Ta                            | -                 |
| Led lifetime                  | 50000 h (L90/B50) |
| Ambient temperature range     | -10 ~50°C         |
| UGR                           | -                 |
| ULR                           | -                 |
| Photobiological Risk group    | No                |
| THDI                          | -                 |
| Fixing kit                    | Yes               |
| With sensor                   | No                |
| With IP55 socket              | No                |

[Download the installation manual](#)



# Lampioik 4

catalogue 2024 p. 80

ref. 175233105

EAN. 3663660322287

Model 1



## Materials and finishes

|          |                            |
|----------|----------------------------|
| Material | aluminium                  |
| Colour   | Silk grey - 105 - RAL 7044 |

## Logistic data

|                      |                   |
|----------------------|-------------------|
| Product dimensions   | H.883 L.452 P.720 |
| Net weight           | 0.000 Kg          |
| Gross weight         | 0.000 Kg          |
| Package dimensions 1 | H.790 L.610 P.500 |

## Certifications and warranties

|                |                         |
|----------------|-------------------------|
| CE             | Yes                     |
| UL             | No                      |
| EAC            | Yes                     |
| RoHS           | Yes                     |
| ENEC           | No                      |
| Anti-corrosion | 25 years (on Aluminium) |
| Technical      | 5 years                 |
| Electronics    | 5 years                 |