

## Technical data

|                               |                      |
|-------------------------------|----------------------|
| Rated voltage                 | 230V AC              |
| Input voltage range           | 100 - 240 V AC       |
| Class                         | 2                    |
| IP                            | 65                   |
| IK                            | -                    |
| Diffuser                      | Clear PMMA           |
| Bulb cover                    | No                   |
| Source                        | Built-in LED         |
| Color temperature real output | 4000°K neutral white |
| Real light output             | 414 lm               |
| Total consupction             | 8 W                  |
| Energy class                  | F (Source LED)       |
| Luminous efficacy             | 52                   |
| IRC                           | 75                   |
| SDCM                          | -                    |
| Dimmable                      | No                   |
| Ta                            | -                    |
| Led lifetime                  | > 70000h (L90/B50)   |
| Ambient temperature range     | -10 ~50°C            |
| UGR                           | -                    |
| ULR                           | -                    |
| Photobiological Risk group    | No                   |
| Fixing kit                    | Yes                  |
| With sensor                   | No                   |
| With IP55 socket              | No                   |

[Download the installation manual](#)



### Materials and finishes

|          |                                |
|----------|--------------------------------|
| Material | aluminium                      |
| Colour   | Sulfur yellow - 068 - RAL 1016 |

### Logistic data

|                      |                  |
|----------------------|------------------|
| Product dimensions   | H.125 L.125 P.64 |
| Net weight           | 1.021 Kg         |
| Gross weight         | 1.100 Kg         |
| Package dimensions 1 | H.130 L.130 P.80 |

### Certifications and warranties

|                |                         |
|----------------|-------------------------|
| CE             | Yes                     |
| UL             | No                      |
| EAC            | Yes                     |
| RoHS           | Yes                     |
| ENEC           | No                      |
| Anti-corrosion | 25 years (on Aluminium) |
| Technical      | 5 years                 |
| Electronics    | 5 years                 |