

Technical data

Rated voltage	230V AC
Input voltage range	220 - 240 V AC
Driver output	-
Alimentation output	-
Class	1
IP	44
IK	-
Diffuser	one-piece clear glass
Bulb cover	-
Source	Built-in LED
Color temperature real output	2700°K warm white
Real light output	446 lm
Total consupction	10 W
Energy class	A++ / A
IRC	>80
SDCM	-
Optic	-
Dimmable	No
Ta	-
Led lifetime	50000 h (L90/B50)
Ambient temperature range	-10 ~50°C
UGR	-
ULR	-
Photobiological Risk group	-
THDI	-
Fixing kit	Yes
With sensor	No
With IP55 socket	No

[Download the installation manual](#)



Louvre

catalogue 2024 p. 218

ref. 133108019

EAN. 3663660310345

Model 4



Materials and finishes

Material	aluminium
Colour	British green - 019 - RAL 6009

Logistic data

Product dimensions	H.436 L.287 P.162
Net weight	0.000 Kg
Gross weight	0.000 Kg
Package dimensions 1	H.470 L.350 P.200

Certifications and warranties

CE	Yes
UL	No
EAC	Yes
RoHS	Yes
ENEC	No
Anti-corrosion	25 years (on Aluminium)
Technical	5 years
Electronics	5 years