

Tetra

catalogue 2024 p. 48

ref. 162031101

EAN. 3663660274449

Model 4



Technical data

Rated voltage	200 to 240 - 50/60Hz
Input voltage range	230 - 250 V AC
Driver output	-
Alimentation output	-
Class	1
IP	65
IK	10
Diffuser	Clear polycarbonate
Bulb cover	Stainless steel
Source	E27
Color temperature real output	-
Real light output	- lm
Total consumption	- W
Energy class	Classe de la lampe (non fournie)
Luminous efficacy	-
IRC	-
SDCM	-
Optic	-
Dimmable	-
Ta	-
Led lifetime	-
Ambient temperature range	-10 ~50°C
UGR	-
ULR	-
Photobiological Risk group	RG0
THDI	-
Fixing kit	Yes
With sensor	No
With IP55 socket	Yes

[Download the installation manual](#)



Tetra

catalogue 2024 p. 48

ref. 162031101

EAN. 3663660274449

Model 4



Materials and finishes

Material	aluminium
Colour	Pure white - 101

Logistic data

Product dimensions	H.1100 L.170 P.100
Net weight	6.700 Kg
Gross weight	7.670 Kg
Package dimensions 1	H.1140 L.200 P.130

Certifications and warranties

CE	Yes
UL	No
EAC	Yes
RoHS	Yes
ENEC	No
Anti-corrosion	25 years (on Aluminium)
Technical	5 years
Electronics	5 years