

*Technical data*

|                               |                         |
|-------------------------------|-------------------------|
| Rated voltage                 | 230V AC                 |
| Input voltage range           | 100 - 240 V AC          |
| Driver output                 | 350mA                   |
| Class                         | 1                       |
| IP                            | 65                      |
| IK                            | 10                      |
| Diffuser                      | Clear polycarbonate     |
| Bulb cover                    | No                      |
| Source                        | Built-in LED            |
| Color temperature real output | 2700°K warm white SYM   |
| Real light output             | 680 lm                  |
| Total consumption             | 12 W                    |
| Energy class                  | -                       |
| Luminous efficacy             | 56,6                    |
| IRC                           | >80                     |
| SDCM                          | 5                       |
| Dimmable                      | No                      |
| Ta                            | -                       |
| Led lifetime                  | 72000 h (L80/B10)       |
| Ambient temperature range     | -10 ~50°C               |
| UGR                           | -                       |
| ULR                           | 1.0%                    |
| Photobiological Risk group    | RG0                     |
| Fixing kit                    | Anchor bolts on request |
| With sensor                   | No                      |
| With IP55 socket              | No                      |

[Download the installation manual](#)

### Materials and finishes

|          |                             |
|----------|-----------------------------|
| Material | aluminium                   |
| Colour   | Fern green - 109 - RAL 6025 |

### Logistic data

|                      |                    |
|----------------------|--------------------|
| Product dimensions   | H.2100 L.170 P.100 |
| Net weight           | 10.540 Kg          |
| Gross weight         | 12.420 Kg          |
| Package dimensions 1 | H.190 L.100 P.2100 |

### Certifications and warranties

|                |                         |
|----------------|-------------------------|
| CE             | Yes                     |
| UL             | No                      |
| EAC            | Yes                     |
| RoHS           | Yes                     |
| ENEC           | No                      |
| Anti-corrosion | 25 years (on Aluminium) |
| Technical      | 5 years                 |
| Electronics    | 3 years                 |