

OL 33

catalogue 2024 p. 132

ref. 144212105

EAN. 3663660250887

Model 4

Technical data

Rated voltage	230V AC
Input voltage range	100 - 240 V AC
Driver output	1050mA
Alimentation output	-
Class	1
IP	65
IK	-
Diffuser	Toughened glass
Bulb cover	No
Source	Built-in LED
Color temperature real output	4500°K neutral white
Real light output	1223 lm
Total consupction	28 W
Standby power	-
Energy class	D (Source LED)
Luminous efficacy	43.7
IRC	80
SDCM	-
Optic	Yes
Dimmable	No
Ta	-
Led lifetime	-
Ambient temperature range	-10 ~50°C
UGR	-
ULR	18%
Photobiological Risk group	-
THDI	-
Fixing kit	Yes
With sensor	No
With IP55 socket	No

[Download the installation manual](#)



OL 33

catalogue 2024 p. 132

ref. 144212105

EAN. 3663660250887

Model 4



Materials and finishes

Material	aluminium
Colour	Silk grey - 105 - RAL 7044

Logistic data

Product dimensions	H.1035 L.220 P.249
Net weight	5.230 Kg
Gross weight	6.690 Kg
Package dimensions 1	H.1010 L.260 P.300

Certifications and warranties

CE	Yes
UL	No
EAC	Yes
RoHS	Yes
ENEC	No
Anti-corrosion	25 years (on Aluminium)
Technical	5 years
Electronics	3 years