Technical data sheet

Support profile for PV module mounting

Item number: 5900405



Support profile to mount photovoltaic modules on flat and pitched roofs. Flat roof mounting in combination with UniBase universal stand and STK and STL short and long supports. Lockable fastening of the profile on the stand with UniBase AMP adapter. Pitched roof mounting in combination with universal DHU roof hook. Lockable fastening of the profile on roof hooks. Screwable connection of multiple support profiles with LV 45 straight connectors and KV 45 cross-connectors. With 10 mm groove on both sides to accept slide nuts and universal and earthing clamps.

CE

Alu Aluminium

BK Bright

Master data


Item number	5900405
Description 1	Truss profile
Description 2	for flat/pitched roof system
Manufacturer	OBO
Dimension	40x45x2350
Colour	aluminium
Material	Aluminium
Surface Surface standard	Bright
Smallest sales unit	4
Unit of quantity	Piece
Weight	242.52 kg
Weight unit	kg/100 pc.

Technical data sheet

Support profile for PV module mounting

Item number: 5900405

Dimensions



Length	2,350 mm
Width	40 mm
Height	45 mm

Technical data

Cable duct, integrated	no
Cable duct optional	no
Section modulus Sx	3680 mm³
Section modulus Sy	3760 mm³