
Technical data sheet

Cable trunking AX 16, trunking width 32, with partition

Item number: 6131213



AXIS Mini cable trunking for covered cable routing in internal areas.
Trunking base with base perforation for direct mounting on the wall and partition to install different voltage levels.
Base and cover as set.

PVC Polyvinylchloride

Master data


Item number	6131213
Description 1	Cable trunking
Description 2	AXIS MINI SET 16x32 Sep.
Manufacturer	OBO
Colour	Pure white; RAL 9010
Material	Polyvinylchloride
Smallest sales unit	56
Unit of quantity	Metre
Weight	22.3 kg
Weight unit	kg/100 m
CO Footprint (GWP) Cradle-to-Gate	0,3736 kg COe / 1 Meter

Technical data sheet

Cable trunking AX 16, trunking width 32, with partition

Item number: 6131213

Dimensions



Length	2,000 mm
Width	32 mm
Height	16 mm

Technical data

Number of fixed partitions	0
Number of insertable partitions	0
Version, cable trunking cover	Loose
Fastening type	Base perforation
Maintain electrical functions	no
Halogen-free	no
Cable retaining clip	no
Duct connector	no
Delivery on a roll	no
Usable cross-section	350 mm²
Protection rating	IP40
Protective film	no
Protection rating IK code	IK07.
Permitted temperature range, max.	60 °C
Permitted temperature range, min.	-5 °C
Transparent	no