



Product features

- 3-step multipower and dual CCT 3000/4000K
- Homogenous light output
- Long lifetime of 50.000h L80B10 at Ta 25°C
- Microwave motion sensor kit available with master-slave function of maximum 250W
- Emergency kit available with 300lm output energy backup lasting for 3 hours



Applications

- Corridor
- Hotel
- Foyer
- Workshop
- Residence

Product information

	Item No.	Description	Power (W)	Lumen (lm)	Light efficacy (lm/W)	CCT (K)	Beam angle (°)	Dimmable
	712193	RENZO Ø500 On/off	14/20/30	1330/1900/2850 1400/2000/3000	95/95/95 100/100/100	3000 4000	120	No

Electrical data

Max. number of luminaires per miniature circuit breaker

Item No.	THD	Inrush current I _{peak} (A)	Inrush current time (μs)	B10	B16	C10	C16	Surge protection (V)
712193	<20%	14	600	8	12	13	21	1000

Ceiling

General specifications

Electrical data	
Nominal voltage	220-240V
Frequency	50/60Hz
Power factor (PF)	>0,9
Protection class	Class I
Photometric data	
CRI	RA80
UGR	N/A
Colour consistency (SDCM)	6
Flicker percentage	≤3% @100Hz
Photobiological safety group	RG0
Mounting & application	
Mounting method	Surface mounted
Loop-through	Yes
Driver	Integrated
IP rating	IP44
IK rating	IK03
Glow wire test	650°C
Lifetime	50000h L80B10 at 25°C
Switching cycles	100000
Operating temperature	-30 to 40°C
Warranty	5 years
Materials	
Material	Steel, PMMA
Certificates	
Standards	CE

Product dimensions & weight

Item No.	Cut-out Ø (mm)	Ø (mm)	H (mm)	Net weight (kg)
712193	N/A	500	130	1,23

Master box information

Item No.	Units / master box	L (mm)	W (mm)	H (mm)	Gross weight (kg)
712193	5	707	539	544	10.789



Accessories

Item No.	710286/ 200030	710354/ 710267									
	Sensor kit	Emergency kit									
712193											