



Product features

- A cost-effective solution offering excellent value for money
- 3-step multipower (12/18/24W) and 3-step CCT (3000/4000/5700K)
- Anti-UV PC cover
- Schutzart IP65 und Schlagfestigkeit IK10
- Microwave motion sensor kit available with standby dimming and master-slave function



MULTI CCT



IK10



CLASS II



30000h L70



Applications

- Parking garage
- Warehouse
- Industrial area
- Staircase
- Garden
- Patio

Product information

	Item No.	Description	Power (W)	Lumen (lm)	Light efficacy (lm/W)	CCT (K)	Beam angle (°)	Dimmable
	712992	BH LYRA Dimlink 3MP 12-24W 830-840-857 IP65 IK10	12/18/24	1320/1980/2640 1500/2250/3000 1320/1980/2640	110 125 110	3000 4000 5700	110	Standby dimming via optional sensor 712873, 0% - 20%

Electrical data

Max. number of luminaires per miniature circuit breaker

Item No.	THD	Inrush current I _{peak} (A)	Inrush current time (μs)	B10	B16	C10	C16	Surge protection (V)
712992	0.41	12	190	20	32	33	35	1000

General specifications

Electrical data	
Nominal voltage	220-240V
Frequency	50/60Hz
Power factor (PF)	0.9
Protection class	Class II
Photometric data	
CRI	RA80
UGR	N/A
Colour consistency (SDCM)	6
Flicker percentage	≤5% @100Hz
Photobiological safety group	RG0
Mounting & application	
Mounting method	Surface mounted
Loop-through	Yes
Driver	Integrated
IP rating	IP65
IK rating	IK10
Glow wire test	650°C
Lifetime	30000h L70B50 at 25°C
Switching cycles	100000
Operating temperature	-20 to 40°C
Warranty	3 years
Materials	
Material	PC, Anti-UV PC
Certificates	
Standards	CE

Product dimensions & weight

Item No.	Cut-out Ø (mm)	Ø (mm)	H (mm)	Net weight (kg)
712992	N/A	300	69	0,73

Master box information

Item No.	EAN code	Units / master box	L (mm)	W (mm)	H (mm)	Gross weight (kg)
712992	4892657129922	10	765	320	325	18.2



Accessories

Item No.	712873										
	Sensor kit										
712992											